

# NorthQ

Q-Door Installation Guide

*v1.1*

Thank you for buying a NorthQ product. Our devices gives you and your family the opportunity to experience ***a new way of living.***

This user manual helps you to get ***Q-Door*** installed. The installation can be performed using PC, Tablet or Smart Phone.

In order to use the ***Q-Door*** with ***HomeManager*** you need to have a NorthQ gateway (***Q-Stick***, ***Q-Gate*** or ***Q-Gate Pro***).



# *1.Q-Door Installation*

**Q-Door** is an innovative door sensor and when in **Armed Mode** settings, it sends an **an alert** whenever a door or a window is opened. Additionally, it detects changes in **humidity**, **temperature** and **light**.



1 Go to **HomeManager** menu

Home Sweet Home

Dashboard

Notifications 45

Consumption

Control

Install

Settings

Sign Out

2 Select **Install**

3 Select **Q-Motion**

4 Click on **Next**

Please install the gateway first (Q-Stick, Q-Gate, Q-Gate Pro).

### Add-Ons

Q-Stick | NQ-930-EU

Q-Gate | NQ-901-EU

Q-Gate Pro | NQ-910-EU

Q-Power | NQ-9021-EU

Q-Gas | NQ-9121-EU

Q-Plug | NQ-9300-EU

Q-Motion | NQ-9700-EU

Q-Door | NQ-9720-EU

Q-Smoke | NQ-9740-EU

Q-Leak | NQ-9760-EU

Danfoss Living Connect | NQ-500-EU

Vision Door/Window Sensor | NQ-Door-Window

Vision PIR Sensor | NQ-PIR

Vision Siren | NQ-Siren

Vision CO Detector | NQ-CO

Cameras | NQ-Cameras

Qubino Relay | NQ-Relay

Heavy Duty Switch | NQ-HD-Switch

In-wall Switch | NQ-9770-EU

Horstmann Thermostat | NQ-HRT4-ZW

Horstmann Relay | NQ-ASR-ZW

Fibaro Wall Plug | NQ-FWP-ZW



Next

5 Insert the **batteries**

6 Click on **start pairing**

7 Press the **button 3 times**

The first step for installing an add-on device is pairing it with a gateway. Please follow the steps below in order to pair it with any one of your gateways. It is recommended that, during the pairing process, the device be at a maximum distance of 1 meter from any of your gateways.



1. Insert the CR14250 battery into the battery compartment.


Make sure the batteries are placed correctly and the device is on. You can now proceed with pairing the device with your gateway by first pressing the START PAIRING button.

Start Pairing



2. Press the program switch 3 times fast using the paper clip in the package.

If the gateway can not find the sensor within 2 minutes, please repeat this step.



1. Insert the CR14250 battery into the battery compartment.  
Make sure the batteries are placed correctly and the device is on. You can now proceed with pairing the device with your gateway by first pressing the START PAIRING button.
2. Press the program switch 3 times fast using the paper clip in the package.  
If the gateway can not find the sensor within 2 minutes, please repeat this step.

3. Once the device is successfully paired, press the NEXT button to continue the installation.

✓ Q-Door successfully paired

Next

8 Check if device is **paired**

9 Click on **Next**



10 Insert **Sensor Name**

11 Assign Sensor to **a Room**

10 Click on **Next**

Insert a sensor name and assign it to a room.

Sensor name

Please enter a preferred name for the sensor.

Assign to a room

Default

Next

**11** *Mount the sensor in the room*

Use the adhesive tape to mount the sensor on the door/window frame.

The magnet has to be mounted at a maximum distance of 1.9 cm from the sensor.


**12** *Click on **Finish***

## Q-Door

## Setup

## 1. Configuring

## 2. Mounting

**1. Mounting the sensor.**

Fix the sensor on the desired location. Using the adhesive tape in the package, mount the sensor on the door/window frame.

**2. Mind the distance.**

Fix the magnet by using either the adhesive tape or the bracket (picture). The magnet has to be mounted on the door/window, at a maximum distance of 1.9 cm from the sensor.

# NorthQ

*A New Way of Living*

NorthQ ApS

Strandvejen 157 | 2900 Hellerup | **Denmark**  
**email:** [support@northq.com](mailto:support@northq.com) | **website:** [www.northq.com](http://www.northq.com)